STREMULIGHT

PRODUCT FACT SHEET

<u>SEPTOR® LED HEADLAMP</u> ALKALINE AAA BATTERY-POWERED HEADLAMP

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Automotive, Sporting Goods, Consumer,

Emergency Medical Services, Safety, Pest Control, Boating, Aviation.

DESCRIPTION: The light weight Septor® headlamp with elastic adjustable head strap features seven (7) Ultra

bright white LEDs for wide task lighting and three power modes. It is also equipped with a low

battery warning indicator.

CASE MATERIAL: Tough ABS thermoplastic plastic construction with elastomer over mold. Available in Yellow.

DIMENSIONS: Face Cap Diameter: 1.75 in. (4.45 cm)

Maximum Width: 2.70 in. (6.85 cm)

Maximum Depth: (Includes head strap mounting plate) 2.40 in. (6.09 cm)

WEIGHT: 5.50 oz (156.0 grams) with batteries (included with purchase).

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: Seven (7) 5mm Ultra Bright White LEDs, impervious to shock with 100,000 hour lifetime.

LIGHT OUTPUT: (7) LEDs - 120 Lumens, 900 candela peak beam intensity, and 60 meter beam distance. (3) LEDs - 45 Lumens, 375 candela peak beam intensity, and 35 meter beam distance.

(1) LED - 13 Lumens, 100 candela peak beam intensity, and 20 meter beam distance.

ON/OFF: Push button switch - Sequences through (1) LED, (3) LEDs, (7) LEDs and Off.

RUN TIME: See chart for run time data. All runtime claims are to 10% of initial lumen output.

BATTERY: Three (3) "AAA" size, Alkaline batteries.

FEATURES: LED technology for extreme brightness.

Low Battery Indicator - Red LED flashes when battery voltage is low and batteries are near the end

of their usable life. LED is located in the reflector in between the "Low Batt" marking and

functions while the light is energized. IPX4 rated for water resistant operation. 2 meter impact resistance tested.

90° tilting head.

Rubber hard hat strap. (Included with purchase)

APPROVALS: (SGS) Class 1, Division 2, Groups A,B,C,D; Class II, Division 2, Groups F,G; Class III, Temp Code: T5

Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: N/A


OUTPUT

RUNTIME

DISTANCE

INTENSITY

FL1 STANDARD	7 LEDS	3 LEDS	1 LED
3,15	120 LUMENS	45 LUMENS	13 LUMENS
	3.5h	10h	55h
N	60m	35m	20m
	900cd	375cd	100cd



Issued: 10/01/2004

Revised: 04/07/2017 Rev: 7 Made In China Document #129