





3M™ Roloc™ Discs

3M™ Cubitron™ II Fibre Disc 987C ■

- 3M precision-shaped grain, engineered with ultra-sharp, fast cutting points that wear evenly, run cool, and optimize mineral breakdown to maximize life
- Best in class for weld prep and removal on heat sensitive alloys such as stainless steel




| UPC | Size | Grade | Qty |
|---|------|-------|--------|
| Roloc™ TR (Plastic Button)  | | | |
| 051125-94952-1 | 2" | 36+ | 50/200 |
| 051125-94957-6 | 2" | 60+ | 50/200 |
| 051125-94962-0 | 2" | 80+ | 50/200 |
| 051125-94953-8 | 3" | 36+ | 50/200 |
| 051125-94958-3 | 3" | 60+ | 50/200 |
| 051125-94963-7 | 3" | 80+ | 50/200 |
| 051125-94954-5 | 4" | 36+ | 25/100 |
| 051125-94959-0 | 4" | 60+ | 25/100 |
| 051125-94964-4 | 4" | 80+ | 25/100 |
| Roloc™ TSM (Metal Button)  | | | |
| 051125-94955-2 | 2" | 36+ | 50/200 |
| 051125-94960-6 | 2" | 60+ | 50/200 |
| 051125-94965-1 | 2" | 80+ | 50/200 |
| 051125-94956-9 | 3" | 36+ | 50/200 |
| 051125-94961-3 | 3" | 60+ | 50/200 |
| 051125-94966-8 | 3" | 80+ | 50/200 |
| Roloc™ TS (Plastic Button)  | | | |
| 051125-87217-1 | 4" | 36+ | 25/100 |
| 051125-87218-8 | 4" | 60+ | 25/100 |
| 051125-87219-5 | 4" | 80+ | 25/100 |

3M™ Cubitron™ II Roloc™ Durable Edge Disc 947A ■ ■



- Features 3M precision-shaped grain
- Great for deburring, blending, cleaning, and finishing applications
- Loading resistant resulting resistant resulting in a faster cut and longer lasting
- Quick-change capability



| UPC | Diameter | Grade | Max RPM | Min/Case |
|---|----------|-------|---------|----------|
| Roloc™ TR (Plastic Button)  | | | | |
| 051141-54239-3 | 1-1/2" | 40+ | 30,000 | 50/200 |
| 051141-54255-3 | 1-1/2" | 80+ | 30,000 | 50/200 |
| 051141-54247-8 | 1-1/2" | 60+ | 30,000 | 50/200 |
| 051141-54263-8 | 1-1/2" | 120+ | 30,000 | 50/200 |
| 051141-54240-9 | 2" | 40+ | 25,000 | 50/200 |
| 051141-54248-5 | 2" | 60+ | 25,000 | 50/200 |
| 051141-54256-0 | 2" | 80+ | 25,000 | 50/200 |
| 051141-54264-5 | 2" | 120+ | 25,000 | 50/200 |
| 051141-54241-6 | 3" | 40+ | 20,000 | 50/200 |
| 051141-54249-2 | 3" | 60+ | 20,000 | 50/200 |
| 051141-54257-7 | 3" | 80+ | 20,000 | 50/200 |
| 051141-54265-2 | 3" | 120+ | 20,000 | 50/200 |


■ Mild Steel ■ Stainless Steel



3M™ Cubitron™ II Roloc™ Durable Edge Disc 947A (cont)

| UPC | Diameter | Grade | Max RPM | Min/Case |
|---|----------|-------|---------|----------|
| Roloc™ TR (Plastic Button)  | | | | |
| 051141-54242-3 | 4" | 40+ | 12,000 | 25/100 |
| 051141-54250-8 | 4" | 60+ | 12,000 | 25/100 |
| 051141-54258-4 | 4" | 80+ | 12,000 | 25/100 |
| 051141-54266-9 | 4" | 120+ | 12,000 | 25/100 |
| Roloc™ TSM (Metal Button)  | | | | |
| 051141-54243-0 | 1-1/2" | 40+ | 30,000 | 50/200 |
| 051141-54251-5 | 1-1/2" | 60+ | 30,000 | 50/200 |
| 051141-54259-1 | 1-1/2" | 80+ | 30,000 | 50/200 |
| 051141-54267-6 | 1-1/2" | 120+ | 30,000 | 50/200 |
| 051141-54244-7 | 2" | 40+ | 25,000 | 50/200 |
| 051141-54252-2 | 2" | 60+ | 25,000 | 50/200 |
| 051141-54260-7 | 2" | 80+ | 25,000 | 50/200 |
| 051141-54268-3 | 2" | 120+ | 25,000 | 50/200 |
| 051141-54245-4 | 3" | 40+ | 20,000 | 50/200 |
| 051141-54253-9 | 3" | 60+ | 20,000 | 50/200 |
| 051141-54261-4 | 3" | 80+ | 20,000 | 50/200 |
| 051141-54269-0 | 3" | 120+ | 20,000 | 50/200 |
| 051141-54246-1 | 4" | 40+ | 12,000 | 25/100 |
| 051141-54254-6 | 4" | 60+ | 12,000 | 25/100 |
| 051141-54262-1 | 4" | 80+ | 12,000 | 25/100 |
| 051141-54270-6 | 4" | 120+ | 12,000 | 25/100 |

3M™ Cubitron™ II Roloc™ Durable Edge Disc 984F ■ ■

- Made with revolutionary 3M precision-shaped grain technology
- Features a durable edge backing and a grinding aid
- For grinding, blending and deburring of light to medium pressure applications for virtually all metal types



| UPC | Diameter | Grade | Max RPM | Min/Case |
|---|----------|-------|---------|----------|
| Roloc™ TR (Plastic Button)  | | | | |
| 051141-27700-4 | 1-1/2" | 36+ | 30,000 | 50/200 |
| 051141-27708-0 | 1-1/2" | 60+ | 30,000 | 50/200 |
| 051141-27716-5 | 1-1/2" | 80+ | 30,000 | 50/200 |
| 051141-27701-1 | 2" | 36+ | 25,000 | 50/200 |
| 051141-27709-7 | 2" | 60+ | 25,000 | 50/200 |
| 051141-27717-2 | 2" | 80+ | 25,000 | 50/200 |
| 051141-27702-8 | 3" | 36+ | 20,000 | 50/200 |
| 051141-27710-3 | 3" | 60+ | 20,000 | 50/200 |
| 051141-28218-3† | 3" | 80+ | 20,000 | 50/200 |
| 051141-27703-5 | 4" | 36+ | 12,000 | 25/100 |
| 051141-27711-0 | 4" | 60+ | 12,000 | 25/100 |
| 051141-27719-6 | 4" | 80+ | 12,000 | 25/100 |
| Roloc™ TSM (Metal Button)  | | | | |
| 051141-27704-2 | 1-1/2" | 36+ | 30,000 | 50/200 |
| 051141-27712-7 | 1-1/2" | 60+ | 30,000 | 50/200 |
| 051141-27720-2 | 1-1/2" | 80+ | 30,000 | 50/200 |
| 051141-27705-9 | 2" | 36+ | 25,000 | 50/200 |
| 051141-27713-4 | 2" | 60+ | 25,000 | 50/200 |
| 051141-27721-9 | 2" | 80+ | 25,000 | 50/200 |