












Accessories: 3M™ Roloc™ Systems

| Product | UPC | For Use With | Size/Description | Max RPM | Qty/Case |
|--|----------------|---|---|---------|----------|
| 3M™ Roloc™ TR Disc Pads  | 051144-45101-2 | 3M™ Roloc™ TR Discs  | 1" Diameter; Medium; 1/4–20 INT | 30,000 | 5 |
| | 051144-45099-2 | | 1-1/2" Diameter; Medium; 1/4–20 INT | 30,000 | 5 |
| | 051144-45100-5 | | 1-1/2" Diameter; Hard; 1/4–20 INT | 30,000 | 5 |
| | 051144-45095-4 | | 2" Diameter; Medium; 1/4–20 INT | 25,000 | 5 |
| | 051144-45096-1 | | 2" Diameter; Hard; 1/4–20 INT | 25,000 | 5 |
| | 051144-45097-8 | | 2" Diameter; Extra Hard; 1/4–20 INT | 25,000 | 5 |
| | 051144-45092-3 | | 3" Diameter; Medium; 1/4–20 INT | 18,000 | 5 |
| | 051144-45091-6 | | 3" Diameter; Hard; 1/4–20 INT | 20,000 | 5 |
| | 051144-45093-0 | | 3" Diameter; Extra Hard; 1/4–20 INT | 20,000 | 5 |
| | 051144-45179-1 | | 4" Diameter; Medium; 1/4–20 INT | 12,000 | 5 |
| | 051141-28474-3 | | 4" Diameter; Hard; 3/8–24 INT | 12,000 | 5 |
| | 051141-28475-0 | | 4" Diameter; Extra Hard; 3/8–24 INT | 12,000 | 5 |
| | 051144-83242-2 | | 4" Diameter; Medium; 5/8–11 INT | 12,000 | 5 |
| | 051144-83489-1 | | 4" Diameter; Hard; 5/8–11 INT | 12,000 | 5 |
| | 051144-83980-3 | | 4" Diameter; Extra Hard; 5/8–11 INT | 12,000 | 5 |
| 3M™ Roloc™ Cool Running Disc Pads  | 051144-82974-3 | 3M™ Roloc™ TR Discs  | 2" Diameter; Medium; 1/4–20 INT | 20,000 | 5 |
| | 051141-28711-9 | | 2" Diameter; Hard; 1/4–20 INT | 20,000 | 5 |
| | 051144-82975-0 | | 3" Diameter; Medium; 1/4–20 INT | 12,000 | 5 |
| | 051141-28710-2 | | 3" Diameter; Hard; 1/4–20 INT | 12,000 | 5 |
| | 051111-56479-0 | | 4" Diameter; Hard; 3/8–24 INT | 15,000 | 5 |
| | 051141-28473-6 | | 4" Diameter; Hard; 5/8–11 INT | 15,000 | 5 |
| 3M™ Roloc™ TS or TSM Disc Pads  | 051144-77729-7 | 3M™ Roloc™ TSM Discs and "Screw on" Abrasive Discs  | 1-1/2" Diameter; Medium; 1/4–20 INT | 30,000 | 5 |
| | 051144-77728-0 | | 1-1/2" Diameter; Hard; 1/4–20 INT | 30,000 | 5 |
| | 051144-14211-8 | | 2" Diameter; Medium; 1/4–20 INT | 25,000 | 5 |
| | 051144-14212-5 | | 2" Diameter; Hard; 1/4–20 INT | 25,000 | 5 |
| | 051144-14215-6 | | 3" Diameter; Medium; 1/4–20 INT | 18,000 | 5 |
| | 051144-14216-3 | | 3" Diameter; Hard; 1/4–20 INT | 20,000 | 5 |
| | 051141-28578-8 | | 4" Diameter; Hard; 5/8–11 INT | 12,000 | 5 |
| 1/4" Threaded Shaft  | 051144-45102-9 | 3M™ Roloc™ Disc Pads with 1/4–20 INT | 1/4" x 1/4–20 Thread | N/A | 10/50 |
| 3M™ Roloc™ + Holder  | 048011-15408-4 | 3M™ Roloc™ Unitized Wheels, Roloc™+ Products, Brush and Disc Accessories | 1" Diameter x 1/4" Shaft Diameter | 25,000 | 5 |
| 3M™ Vacuum Hose Anti-Static  | 051141-28730-0 | Used to Connect Random Orbital and Orbital Sanders to a Vacuum System | 1" ID x 4 ft Length, 1" EXT Hose Thread | N/A | 1 |
| 3M™ Overhose Kit  | 051141-28651-8 | 0.3 HP Die Grinders | Kit Contains: Air Line Extension (PN 20209), Adapter (PN 20453), Over Hose Cloth Sleeve, Exhaust Spacer, Air Inlet Bushing, Instruction Sheet | N/A | 1 |
| Mini Sander | | | | | |
| 3M™ Finesse-it™ Roloc™ Sanding Pads TR  02345 02511 | 051111-50198-6 | Roloc™ Disc Pad or with Tools Equipped with Roloc™ Attachment System | 1-1/4" Diameter; Medium | 10,000 | 20 |
| | 051111-51150-3 | | 1-1/4" Diameter; Firm | 10,000 | 20 |