

Guide for 3M[™] ANSI Hard Hats, Headgear, and Faceshields



				31	Л ™ H-Series Ha	rd Hats/Headge	ear				3M™ SecureFit™ Safety Helmet
	H24M	H24T	H18	H18-S	H8A	H10	H8A-S	H700	H800	H700T	X5000
		8									
3M ID	7000002292	7100113761	7000002291	7000052752	7000002290	7000052751	7000127237	Various	Various	Various	Various
Product ID	H24M	H24T	82502-00000	82536-00000	82501-00000	82516-00000	82589-00000	Various	Various	Various	Various
Key Benefits	Hard Hat Faceshield Holder, Allows use of slots for hard hat mounted ear muffs	Heat Resistant Hard Hat Faceshield Holder, Allows use of slots for hard hat mounted ear muffs	Hard Hat Slot Mounted Faceshield Holder	Hard Hat Slot Mounted, Heat Resistant Faceshield Holder	Standard Faceshield Holder	Extended Crown Coverage Faceshield Holder	Heat Resistant Faceshield Holder	Cap Style	Full Brim	Cap Style, Elevated Temperature	Climbing Style
Suspension Options Ratchet R Pinlock P					R	R	R	RP	R	R	R
Spark Def/Shell Material	ABS	Glass Nylon	ABS	Triax	ABS	ABS	Triax	HDPE	HDPE	Glass Nylon	ABS
Radiant Heat Resistance (Temperatures above standard test temperatures of 120°F [49°C])	170°F (82°C)	375°F (190°C) Radiant Heat		300°F (149°C) Reflective	170°F (82°C)	170°F (82°C)	300°F (149°C) Reflective			375°F (190°C) Radiant Heat	
Non-Vented Models Available with ANSI Electrical Insulation								CLASS CLASS E	CLASS CLASS E	CLASS	CLASS CLASS E
Color	Blue/Silver	Black/Silver	Blue Spark Deflector	Silver Spark Deflector, Gray Suspension	Blue Spark Deflector, Gray Suspension	Blue Crown/Spark Deflector, Gray Suspension	Silver Spark Deflector, Gray Suspension	•••••	•••••	••0	•••••
Approximate Weight	4.8 oz (136 grams)	4.8 oz (136 grams)	5.5 oz (150 g)	5.5 oz (150 g)	7.5 oz (212 g)	9 oz (255 g)	7.5 oz (212 g)	12 oz (343 g) Pinlock / 13 oz (366 g) Ratchet / Plus 0.3 oz (8.5 g) 6 pt	13 oz (380 g) Pinlock / 14 oz (403 g) Ratchet / Plus 0.3 oz (8.5 g) 6 pt	13 oz (375 g) ratchet	Vented w/ magnetic chinstrap: 17 oz (472 g) Nonvented w/ plastic chinstrap: 16 oz (453 g) Suspension: 2.5 oz (70 g)
Suspension Size					6-3/4 in. to 8 in. (17 cm to 20 cm)	6-3/4 in. to 8 in. (17 cm to 20 cm)	6-3/4 in. to 8 in. (17 cm to 20 cm)	6-5/8 in. to 7-3/4 in. (17 cm to 20 cm)	6-5/8 in. to 7-3/4 in. (17 cm to 20 cm)	6-5/8 in. to 7-3/4 in. (17 cm to 20 cm)	6-1/4 in. to 7-7/8 in. (17 cm to 20 cm)
ANSI Z87 Approved with Faceshield	•	V	V	V	V	V	V				
ANSI Z89.1 Impact Rating								TYPE	TYPE	TYPE	TYPE
ANSI Lower Temp Rating (LT)								Tested to -22°F (-30°C)	Tested to -22°F (-30°C)		Tested to -22°F (-30°C)
ANSI Higher Temp Rating (HT)										Tested to 140°F (60°C)	
ANSI Reverse Donning								V	•	V	V
Optional Logo/Reflective hardhatcustomizer.3M.com								LOGO REF	LOGO REF	LOGO REF	LOGO REF
3M™ UVicator™ Sensor Models Available Lets wearer know when to replace hard hat due to UV exposure								•	⊘		~

		rating of 23.	,		paratery. Fras With Fatting Of 25.	all Will of 20 of Floria					ig, and painting.						hard hat due	e to UV exposure	•										
		Product Number	3М ІД	Product ID	Marketplace Formal Name	Potential Application	Key Benefits	Attachments Included Each/C	Faceshield Material	Molded/ Flat	Thickness	Height	Width	ANSI High Impact (Z87+)	Outer Coating	Inner Coating	Chemical Resistant	ANSI Light Filters	Temp Rating of FS Material				Adapter	s for Hard H	lats/headg	ear and faceshie	ds/screens		
		W96	710000026	82700- 00000	Clear Propionate Faceshield W96, Face Protection 82700-00000, Molded	Chemical industry; Spray painting	Chemical Resistant	10	Propionate	Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)				O		210°F/98°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96	700000233	9 82701-	Clear Polycarbonate Faceshield WP96, Face Protection 82701-00000, Molded	Heavy industry; Construction; Metal working; Grinding	Standard	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	⊘				U6	266°F/130°C	N	0	Adap	ter	Ne	ec	led	H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96X	7000127230	82582-	Wide Clear Polycarbonate Faceshield WP96X, Face Protection 82582-00000, Flat Stock	Heavy industry; Construction; Metal working; Grinding	Extended Side Coverage	25	Polycarbonat	e Flat	0.04 in. (0.1 cm)	18.25 in. (46 cm)	9 in. (23 cm)	✓				U6	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WE96X	700012723	82581-	Wide Clear PETG Faceshield WE96X, Face Protection 82581-00000, Flat Stock	Chemical industry; Spray painting	Chemical Resistant, Extended Side Coverage	25	PETG	Flat	0.04 in. (0.1 cm)	18.25 in. (46 cm)	9 in. 23 cm)						176°F/80°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WE96S	7000127234	82580-	Short Clear PETG Faceshield WE96S, Face Protection 82580-00000, Flat Stock	Manufacturing	Chemical Resistant, Shorter Length, Reduces Fogging	50	PETG	Flat	0.04 in. (0.1 cm)	14.5 in. (37 cm)	7.5 in. (19 cm)				⊘		176°F/80°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
	0	WP96B	700012723	82525-	Polycarbonate Molded Medium Green Faceshield Window WP96B, Face Protection 82525-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Tinted for Moderately Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)					U6 S	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
	6	WP96C	700000234	82702-	Dark Green Polycarbonate Faceshield WP96C, Face Protection 82702-00000, Molded	Heavy industry; Construction; Metal working; Grinding, Foundries	Tinted for Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	✓				U6 S	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96AL	700005270	82504- 00000	Aluminized Polycarbonate Molded Clear Faceshield Window, Face Protection 82504-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Blocks IR	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)		Aluminum			U6 W3.0	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96BAL	700005270	82518-	Medium Green Aluminized Polycarbonate Faceshield WP96BAL, Face Protection 82518-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Blocks IR Tinted for Moderately Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	✓	Aluminum			U6 W5	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96CAL	700012716	82509-	Aluminized Polycarbonate Molded Dark Green Faceshield Window, Face Protection 82509-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Blocks IR Tinted for Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)		Aluminum			U6 W7	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
W-Series		WP96IR3	7000127240	82705-	Polycarbonate Faceshield Window W96IR3, Face Protection 82705-10000, Shade 3.0	Heavy industry; Construction; Metal working; Grinding, Foundries	Blocks up to 91% of IR Radiation	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14 in. (37 cm)	9 in. (23 cm)	✓				U6 W3.0	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WP96IR5	700012724	82706- 10000	Polycarbonate Faceshield Window W96IR5, Face Protection 82706-10000, Shade 5.0	Heavy industry; Construction; Metal working; Grinding, Foundries	Blocks up to 97.5% of IR Radiation	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	\bigcirc				U6 W5	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WCP96	700005275	82600-	Total Performance Polycarbonate Clear Faceshield Window WCP96, Face Protection 82600-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Abrasion and Fog Resistant Coatings	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	✓	Anti Scratch	Anti-fog		U6	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		WCP96B	701038406	82601- 00000	Total Performance Polycarbonate Medium Green Faceshield Window WCP96B, Face Protection 82601-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Tinted for Moderately Bright Environments & Abrasion and Fog Resistant Coatings	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	\bigcirc	Anti Scratch	Anti-fog		U6 S	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
reens ¹		WCP96G	700012723	82602-	Total Performance Gold-coated Polycarbonate Clear Faceshield Window WCP96G, Face Protection 82602-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Higher IR Block	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	✓	Gold & Anti Scratch	Anti-fog		U6 W3.0	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
hields/Sc		WCP96BG	700014493	9 82603- 00000	Total Performance Gold-coated Polycarbonate Medium Green Faceshield Window WCP96BG, Face Protection 82603-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Higher IR Block Tinted for Moderately Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	⊘	Gold & Anti Scratch	Anti-fog		U6 W5	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
Faces		WCP96CG	700012723	82604-	Total Performance Gold-coated Polycarbonate Dark Green Faceshield Window WCP96CG, Face Protection 82604-00000	Heavy industry; Construction; Metal working; Grinding, Foundries	Higher IR Block Tinted for Bright Environments	10	Polycarbonat	e Molded	0.08 in. (0.2 cm)	14.5 in. (37 cm)	9 in. (23 cm)	✓	Gold & Anti Scratch	Anti-fog		U6 W7	266°F/130°C								H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
	+	WP98	700000233	7 82543-	Clear Polycarbonate Faceshield WP98, Face Protection 82543-00000, Flat Stock	Heavy industry; Construction; Metal working; Grinding, Foundries	Additional	10	Polycarbonat	e Flat	0.04 in.	14.5 in. (37 cm)	7.25 in.					U6	266°F/130°C								H24M	H24T H18-S	U5B-ANSI with P3EV/2-10P or
	-	CP8	700012723	82542-	Replacement Clear Chin Protector CP8, Face Protection 82542-00000	N/A Must be used with WP98	Chin Coverage	10	Polycarbonat	e Molded	(0.1 cm)		(18 cm)	•					266°F/130°C								H18	H18-S	Helmet Attached 3M Earmuffs
		W96M	7000127168	82506-	Steel Mesh Faceshield Screen W96M, Face Protection 82506-00000, Molded	Forestry; Agriculture; Brush cutting; Trimming	Good Ventilation	10	Steel Mesh	Molded		14.5 in. (37 cm)	9 in. (23 cm)														H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
_		W96MW	700012723	82511- 00000	Steel Mesh Faceshield Screen W96MW, Face Protection 82511-00000, with Clear Eyeshield	Forestry; Agriculture; Brush cutting; Trimming	Good Ventilation and Clear Window for Improved Visibility	10	Steel Mesh	Molded		14.5 in. (37 cm)	9 in. (23 cm)							<u> </u>		†	+	<u> </u>	1	+	H24M H18	H24T H18-S	U5B-ANSI with P3EV/2-10P or Helmet Attached 3M Earmuffs
		V1A-10P	700010380	8 V1A-10P	PELTOR™ Metal Mesh Faceshield V1A-10P, Face Protection, Black	Forestry; Agriculture; Brush cutting; Trimming	Steel Mesh, Great Ventilation	V010 Linkage 10	Steel Mesh	Molded		11.5 in. (30 cm)	6.5 in. (16.5 cm)														P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
		V1B-10P	700010380	9 V1B-10P	PELTOR™ Nylon Mesh Faceshield V1B-10P, Face Protection, Black	Forestry; Agriculture; Brush cutting; Trimming	Nylon Mesh, Great Ventilation	V010 Linkage 10	Nylon Mesh	Molded		11.5 in. (30 cm)	6.5 in. (16.5 cm)														P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
m		V2A-10P	7000103810) V2A-10P	PELTOR™ Clear Acetate Faceshield V2A-10P Face Protection	Risk of exposure to solid particles / Chemical	Chemical Resistant, Lightweight & Improved Ventilation	V010 Linkage 10	Acetate	Flat	0.04 in. (0.1 cm)	12.125 in. (31 cm)	8.25 in. (21 cm)				O		200°F/93°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
V1/V2/V;		V2B-10P	700010381	V2B-10P	PELTOR™ Green Polycarbonate Faceshield V2B-10P, Face Protection	Heavy industry; Construction; Metal working; Grinding	Tinted for Moderately Bright Environments, Lightweight & Improved Ventilation	V010 Linkage 10	Polycarbonat	e Flat	0.04 in. (0.1 cm)	12.125 in. (31 cm)	8.25 in. (21 cm)	⊘				U6 S									P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
		V2C-10P	7000103812	2 V2C-10P	PELTOR™ Clear Polycarbonate Faceshield V2C-10P, Face Protection	Heavy industry; Construction; Metal working; Grinding	Lightweight & Improved Ventilation	V010 Linkage 10	Polycarbonat	e Flat	0.04 in. (0.1 cm)	12.125 in. (31 cm)	8.25 in. (21 cm)	V				U6	266°F/130°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
		V3C-10P	NA	V3C-10P	PELTOR™ Clear Short Polycarbonate Visor V3C-10P, Face Protection	Manufacturing	Short Visor. Lightweight & Improved Ventilation	V010 Linkage 10	Polycarbonat	e Flat	0.04 in. (0.1 cm)	12.125 in. (31 cm)	6.125 in. (15.5 cm)					U6	266°F/130°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
	1	V3F-10P	7000103814	1 V3F-10P	PELTOR™ Clear Acetate Visor, Face Protection V3F-10P	Manufacturing	Chemical Resistant, Nose Cutout & Improved Ventilation	V010 Linkage 10	Acetate	Flat	0.04 in. (0.1 cm)	12.125 in. (31 cm)	5.5 in. (14 cm)				<u>•</u>		200°F/93°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
	Ű	V4A-10P	7000010381	5 V4A-10P	PELTOR-Steel Mesh MultiVisor™ System V4A-10P Face Protection	Forestry; Agriculture; Brush cutting; Trimming	Steel Mesh, Good Ventilation, Adjustable Face to Shield Distance	V43 Visor Peak Frame and V412 10 Linkage	Metal Mesh	Flat		11.5 in. (30 cm)	6.5 in. (16.5 cm)														P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
47	~	V4D-10P	7000103810	6 V4D-10P	PELTOR™ Clear Acetate MultiVisor™ Faceshield System V4D-10P, Face Protection with Anti-Fog Coating	Forestry; Agriculture; Brush cutting; Trimming	Chemical Resistant, Fog Resistant, Adjustable Face to Shield Distance	V43 Visor Peak Frame and V412 10 Linkage	Acetate	Flat	0.04 in. (0.1 cm)	11.8 in. (29 cm)	7 in. (18 cm)			Anti-fog	•		200°F/93°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
	~	V4F-10P	700010381	7 V4F-10P	PELTOR™ Clear Polycarbonate MultiVisor™ System V4F-10P, Face Protection	Heavy industry; Construction; Metal working; Grinding	Lightweight, Adjustable Face to Shield Distance	V43 Visor Peak Frame and V412 10 Linkage	Polycarbonat	e Flat	0.04 in. (0.1 cm)	11.8 in. (29 cm)	7 in. (18 cm)					U6	266°F/130°C								P3EV/2-10P or Helmet Attached 3M Earmuffs	P3EV/2-10P or Helmet Attached 3M Earmuffs	
																													

							Ea	rMuffs — Compatibl	e with H-700, H-700t	AND X5000 ² — All fe	aceshields listed are	compatible with 3M e	earmuffs (except 2000F	4)						
									3M™ PELTOR™ Earmuffs									3M™ PELTOR™ C	optime™ Earmuffs	3M™ E-A-R™ Earmu
	X1P3E	X2P3E	ХЗРЗЕ	Х4Р3Е	X5P3E	X1P5E	X2P5E	X3P5E	X4P5E-OR	X4P5E	X5P5E	X1P51E	X4P51E	H31P3E	Н7Р3Е	H10P3E	H7P3E-PTL	95	98	2000H
																				60
ID	7000104075	7000104076	7000104077	7000104078	7000104079	7100097525	7100097448	7100097405	7100097526	7100097429	7100097527	7100135816	7100135827	7000141054	700009668	7000002327	7000002317	7000052743	7000002326	7100005737
duct ID	X1P3E	X2P3E/37276(AAD)	X3P3E/37277(AAD)	X4P3E/37278(AAD)	X5P3E37279(AAD)	X1P5E	X2P5E	X3P5E	X4P5E-OR	X4P5E	X5P5E	X1P51E	X4P51E	H31P3E	Н7Р3Е	H10P3E	H7P3E-PTL	H6P3E/V	Н9РЗЕ	330-3031
ketplace mal Name	3M™ PELTOR™ X1P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X2P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X3P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X4P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X5P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X1P5E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X2P5E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X3P5E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X4P5E-OR Earmuffs, Hard Hat Attached	3M™ PELTOR™ X4P5E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X5P5E Earmuffs, Hard Hat Attached	3M™ PELTOR™ X1P51E Earmuffs, Hard Hat Attached, Full Brim	3M™ PELTOR™ X4P51E Earmuffs, Hard Hat Attached, Full Brim	3M™ PELTOR™ H31P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ H7P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ H10P3E Earmuffs, Hard Hat Attached	3M™ PELTOR™ H7P3E-PTL Earmuffs, Hard Hat Attached	3M™ PELTOR™ Optime™ 95 Earmuffs, Hard Hat Attached	3M™ PELTOR™ Optime™ 98 Earmuffs, Hard Hat Attached	3M™ E-A-R™ 2000H Earmuffs, Hard Hat Attached
chments ided	P3EV/2 w/ muffs	P5 w/ muffs	P5 w/ muffs	P5 w/ muffs	P5 w/ muffs	P5 w/ muffs	P5 w/ muffs	P51 w/ muffs	P51 w/ muffs	P3EV/2 w/ muffs	P3EV/2 w/ muffs	P3EV/2 w/ muffs	P3EV/2 w/ muffs	P3EV/2 w/ muffs	P3EV/2 w/ muffs	P5 electrically insluated arm				
/Case	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	24
	21 dBA	24 dBA	25 dBA	25 dBA	31 dBA	21 dBA	24 dBA	25 dBA	25 dBA	25 dBA	31 dBA	21 dBA	26 dBA	23 dBA	24 dBA	27 dBA	25 dBA	21 dBA	23 dBA	21 dBA

	H-Series Hard Hats/Headgear Spare Parts and Accessories													ies Hard Hats/	Headgear and	BM [™] SecureFit [™]	X5000 Spare P	arts and Acces	ssories	3M™ SecureFit™ X5000 Spare Parts and Accessories⁴									
	H-700-RS4	H-700-PS4	H-700-BP	H-700-S6	NC2-GR	FC1-Al	FC1-GR	TCS1	H-SR-S	V43	GR2B-10P	X24	P3EV/2-10P	V901AF	V902AF	V903AF	HL100	HL200	HL300IS	X5-SV01	X5-SV02	X5-SV03	U5B-ANSI	X5-S4PTCS1	X5-P4PTCS1	X5-REFKIT	X5-SWBD01	X5-6PTSUS	
																			100				<u> </u>	P _i	B	JT			
BM ID	7000002421	7000002422	7000030093	7000053150	7010293216	7100082486	7100082485	7100113757	7010341312	7000103846	7000103819	7000029947	7000103847	7100101916	7100205236	7100205235	7010386281	7010316628	7010386282	7100176969	7100176970	7100176971	7100179142	7100175586	7100175588	7100175590	7100180680	7100180703	
roduct ID	H-700-RS4	H-700-PS4	H-700-BP	H-700-S6	NC2-GR	FC1-AI	FC1-GR	TCS1	H-SR-S	V43	GR2B-10P	X24	P3EV/2-10P	V901AF	V902AF	V903AF	HL100	HL200	HL300IS	X5-SV01	X5-SV02	X5-SV03	U5B-ANSI	X5-S4PTCS1	X5-P4PTCS1	X5-REFKIT	X5-SWBD01	X5-6PTSUS	
oduct escription	Replacement Ratchet Suspension, Fits H-700, H-800, and H-700T	Replacement Pinlock Suspension, Fits H-700, H-800, and H-700T	Replacement Browpad, Fits H-700, H-800, and H-700T	Replacement suspension strap to be used with 4-point pinlock or 4-point ratchet suspension for H-700, H-800 and H-700T	Attaches to H-700T Hard Hat to help provide posterior neck protection from molten metal splash	Aluminum Front Helmet Cover	Cotton + Para-aramide Front Helmet Cover	Terry Cloth Sweatband	Reflective Strips for H-700/H-800	MultiVisor Brim, Face Protection, Replacement for Visors	Hard Hat Front Visor Seal GR2B-10P, Head Protection	Elastic Chin Strap X24, Head Protection 46551- 00000 for Helmet H700 and H800	Adaptor for use in Hard Hat slots without PELTOR™ muffs	Integrated Protective Eyewear V901AF Clear Anti-fog Lens, ANSI Z87.1 2015	Integrated Protective Eyewear V902AF Gray Anti-fog Lens, ANSI Z87.1 2015	Integrated Protective Eyewear V903AF Amber Anti-fog Lens, ANSI Z87.1 2015	70 Lumen Task Light	150 Lumen Task Light	150 Lumen Task Light, Intrinsically Safe — Class I, II & III and Div 1 & 2	Short Visor, Clear Anti-Fog Anti-Scratch Polycarbonate, ANSI Z87.1 2015	Short Visor, Grey Anti-Fog Anti-Scratch Polycarbonate, ANSI Z87.1 2015	Short Visor, Amber Anti-Fog Anti-Scratch Polycarbonate, ANSI Z87.1 2015	Faceshield Holder	Standard 4 Point Chin Strap with Buckle	Premium 4 Point Chin Strap with Magnetic Buckle	Reflective Sticker Kit	Black/Grey Replacement Sweat Band for SecureFit Safety Helmet	Replacement 6 Point Suspension for SecureFit Safety Helmet	
ch/Case	20	20	20	20	10	1	1	10	20	1	10	10	5	20	20	20	10	10	10	10	10	10	10	1	1	10	10	10	

3M PSD HEFH 2823 Head & Face Matrix_Poster 38x48.5 v9.1.indd 1

4. Not all accessories are rated for elevated temperatures. For additional product ratings, see product label.



