

## Air Chief A Series Quick-Connect Plugs

**Application:**

- for use in compressed air service where the convenience of one hand operation and a compact profile is desired

**Features:**

- maximum operating pressure: **500 PSI** at ambient temperature (70°F)
- machined from solid brass bar stock
- stainless steel balls and springs maximize corrosion resistance


### Female Pipe Thread

Body Size	Female NPT	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>A1F1-B</b>	20
1/4"	1/4"	brass	25 CFM	<b>A2F2-B</b>	20



### Male Pipe Thread

Body Size	Male NPT	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>A1M1-B</b>	20
1/4"	1/4"	brass	25 CFM	<b>A2M2-B</b>	20



### Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>A1S1-B</b>	20




## Air Chief A Series Quick-Connect Couplers

automatic - push to connect

### Female Pipe Thread

Body Size	Female NPT	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>1AF1-B</b>	20
1/4"	1/4"	brass	25 CFM	<b>2AF2-B</b>	20



### Male Pipe Thread

Body Size	Male NPT	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>1AM1-B</b>	20
1/4"	1/4"	brass	25 CFM	<b>2AM2-B</b>	20



### Hose Barb

Body Size	Hose ID	Material	Flow Rating at 100 PSI	Part #	Opt Qty
1/8"	1/8"	brass	7 CFM	<b>1AS1-B</b>	20
1/4"	1/4"	brass	25 CFM	<b>2AS2-B</b>	20

