

## A-Series Pneumatic Couplings


**Features:**

- Interchange data: Dixon Quick Coupling Proprietary Astronautics
- Nitrile (Buna-N) seals are standard temperature range **-40°F to 250°F (-40°C to 121°C)**

### Female Threaded Plugs



brass



steel

Body Size	Threads	Brass Part #	Steel Part #
1/8"	1/8" - 27 NPTF	<b>A1F1-B</b>	---
1/4"	1/8" - 27 NPTF	<b>A2F1-B</b>	---
	1/4" - 18 NPTF	<b>A2F2-B</b>	<b>A2F2</b>

### Male Threaded Plugs



brass



steel

Body Size	Threads	Brass Part #	Steel Part #
1/8"	1/8" - 27 NPTF	<b>A1M1-B</b>	---
1/4"	1/4" - 18 NPTF	<b>A2M2-B</b>	<b>A2M2</b>

### Hose Barb Plugs



brass



steel

Body Size	Hose ID	Brass Part #	Steel Part #
1/8"	1/8"	<b>A1S1-B</b>	---
1/4"	1/4"	---	<b>A2S2</b>

### Female Threaded Couplers



Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPTF	<b>1AF1-B</b>
1/4"	1/8" - 27 NPTF	<b>2AF1-B</b>
	1/4" - 18 NPTF	<b>2AF2-B</b>

### Male Threaded Couplers



Body Size	Threads	Brass Part #
1/8"	1/8" - 27 NPTF	<b>1AM1-B</b>
1/4"	1/8" - 27 NPTF	<b>2AM1-B</b>
	1/4" - 18 NPTF	<b>2AM2-B</b>