




## ROUND DRUM HOODS 20" – 23" (508 – 584 mm) hoods fit both chimed drums and environmental packs

	Part No.	Description
	WW10204F	20.4" (518 mm) Round Hood only
	WW10204F-DP	20.4" (518 mm) Round Hood with Direct Pull Kit
	WW10231F	23" (584 mm) Round Hood only
	WW10231F-DP	23" (584 mm) Round Hood with Direct Pull Kit
	WW10260F	26" (660 mm) Round Hood only
	WW10260F-DP	26" (660 mm) Round Hood with Direct Pull Kit
	WW10260C-2	26" (660 mm) Round Hood, for chimed drums only
	WW10260DP-2	26" (660 mm) Round Hood with Direct Pull Kit; for chimed drums only

## OCTAGON DRUM HOODS

	Part No.	Description
	WWOC-20.5	20.5" (521 mm) Octagon Hood (500 lb / 227 kg)
	WWOC20.5-DP	20.5" (521 mm) Octagon Hood with Direct Pull Kit
	WWOC-23.5	23.5" (597 mm) Octagon Hood (900 lb / 408 kg)
	WWOC23.5-DP	23.5" (597 mm) Octagon Hood with Direct Pull Kit
	WWOC	23.5" (597 mm) Low Profile Hood (900 lb / 408 kg)
	WWOC-DP	23.5" (597 mm) Low Profile Hood with Direct Pull Kit

## SQUARE DRUM HOODS

	Part No.	Description
	WWSC-21	21" (533 mm) Square Hood (500 lb / 227 kg)
	WWSC21-DP	21" (533 mm) Square Hood with Direct Pull Kit
	WWSC-24	24" (610 mm) Square Hood (1,000 lb / 453 kg)
	WWSC24-DP	24" (610 mm) Square Hood with Direct Pull Kit
	WWSC-29	29" (737 mm) Square Hood (990 lb / 449 kg)


## DODECAGON HOODS & ACCESSORIES for 100 lb (45.4 kg) and 300 lb (136 kg) aluminum wire packages

	Part No.	Description
	WWDO-23.5	23.5" (597 mm) Dodecagon Hood
	A-12A	Connector for EC-4 Conduit

## ADDITIONAL EQUIPMENT

Part No.	Description
WWDP	Direct Pull Kit
WWSB-M12-K	Sensor Block and Proximity Switch Kit
WWSB-M12	Sensor Block (12 mm)
WWA5-E34	Proximity Switch (PNP)
WWA5-E35	Proximity Switch (NPN)
WWIC-11	Reusable Drum Core
WWDI	Conduit Connection Insulator

## ORBITAL ARM KITS with Quick Disconnect

	Part No.	Description
	WWOA-20	Compatible with 20" (508 mm) – 23.4" (594 mm) hood for up to 0.062 (1.6 mm) Steel or Cored Wire
	WWOA-20A	Compatible with 20" (508 mm) – 23.4" (594 mm) hood for up to 3/64" (1.2 mm) Aluminum/Non-ferrous Wire
	WWOA-20H	Compatible with 20" (508 mm) – 23.4" (594 mm) hood for up to 0.062 (1.6 mm) Steel or Aluminum/Non-ferrous Wire

## ORBITAL ARM REPLACEMENT PARTS

Part No.	Description
A-4	(1) Quick Disconnect (QD)
WWRL-H3	(2) Replacement Liner for WWOA-20
WWRL-H4	(2) Replacement Liner with Inlet Guide for WWOA-20H
C-1H	(3) Inlet Guide with Ceramic Insert