

Wire Brushes - Wheel Brushes - Stainless Steel



Flexovit SPECIALIST STAINLESS STEEL WIRE WHEEL BRUSHES are available in three different brush styles. High quality steel wire and rugged construction provide fast, efficient brushing on production work.

Use on Angle Grinders



STAINLESS STEEL:

Stainless Wire: .016, .020: For applications where contamination of the work-piece is a concern.

Stringer Bead Wire Wheel: Narrow work face allows for easy access to confined areas. Ideal for weld and bead cleaning on pipes and vessels.

Dia.	Face Width	Thread	MAX RPM	Stainless Wire .020	Box/Ctn Qty.
4	1/4	5/8-11	20,000	C1180	1/24
4	1/4	M14-2.0	20,000	C1190	1/24
4	1/4	M10-1.25	20,000	C1200	1/24
5	1/4	5/8-11	12,000	C1275	1/24
6-1/2	1/4	5/8-11	12,000	C1120	1/24



Knot Wire Wheel, Regular Twist: 3/8 tufts provide high impact action to remove scale weld and splatter.

Dia.	Face Width	Thread	MAX RPM	Stainless Wire .020	Box/Ctn Qty.
4	3/8	5/8-11	20,000	C1380	1/24
4	3/8	M14-2.0	20,000	C1390	1/24
4	3/8	M10-1.25	20,000	C1400	1/24
4	3/8	M10-1.5	20,000	C1410	1/24
4	3/8	1/2-13	20,000	C1420	1/24
5	3/8	5/8-11	12,000	C1435	1/24



Knot Wire Wheel, Full Cable Twist: Knots are uniform and balanced to withstand heavier impact in sever application.

Dia.	Face Width	Thread	MAX RPM	Stainless Wire .016	Box/Ctn Qty.
4	3/8	5/8-11	20,000	C1265	1/24
6	3/8	5/8-11	9,000	C1105	1/24

