

## Series 300

Continuous handle model is the most popular and versatile. Excellent for construction jobs or large shops. High floor clearance when moving over rough surfaces or cluttered areas. Angle legs remove load from the wheels when truck is stationary. Cylinder hold chain and large bolt on tool box are standard equipment. (Replacement part number TB300) Designed to handle medium and large cylinders. Available with optional "Belly Band" - designate "B" in part number (Example 310B-86). Available with optional "Fire Barrier" - designate "F" in part number (Example 324F-32). Available with optional "Lock Top Tool Box" - designate "LT" in part number (Example 316LT-72). Combination "Lock Top Tool Box" and "Belly Band" (Example 316LTB-72).



### Series 300 Specifications

Model No.	Wheel Diameter and Type	Max. Diameter Oxygen Cyl.	Max. Diameter Acetylene Cyl.	Bracket Chain Ht.	Base Plate Dimension	Height	Width	Weight
312-25	12" x 1.75" Semi-Pneu., Plain	9 1/4"	13 1/2"	27"	13" x 24"	46"	31"	46 lbs.
314-27	14" x 1.75" Semi-Pneu., BB	9 1/4"	13 1/2"	27"	13" x 24"	46"	31"	51 lbs.
316-72	16" x 4" Pneu., BB	9 1/4"	13 1/2"	27"	13" x 24"	46"	35"	59 1/2 lbs.
324-32	24" x 2" Steel, BB	9 1/4"	13 1/2"	27"	13" x 24"	46"	32"	58 1/2 lbs.
Wider frame for large oxygen cylinder and 100 pound propane cylinder								
LP314-27	14" x 1.75" Semi-Pneu., BB	9 1/4"	15 3/4"	27"	13" x 26"	45"	33"	53 lbs.

## ACCESSORIES



### Belly Band

Belly band securely holds cylinders in place. Can be ordered as an option in place of the standard chain. Designate "B" in the part number when ordering. (Example 310B-86). The belly band can be used on Series 150, 300, 400, 900 and 940.

### Tool Boxes

**LT-2** - Optional "Lock Top Tool Box" for 300 series designate "LT" in the part number (Example 316LT-72)  
22" long x 7" wide x 7" deep



**TB300** - Replacement tool box for 300 series  
22" long x 5" wide x 3 3/4" deep



### Fire Barrier

The steel fire barrier has been engineered specifically to meet 1/2 hour fire resistance rating. The barrier meets OSHA standard 1926.350 (a)(10). The OSHA standard states that welding carts equipped with this barrier can be used for storage beyond the 24 hour limit. This fire barrier will fit on all current models 300, 900 and 940 series. Designate "F" in the part number. (Example 324F-32) Replacement part number FB-1.

