

Genuine Miller® Accessories



Female
Receptacle



Full KVA Adapter Cord 300517 Field
NEMA 14-50P to NEMA 6-50R. Adapts engine
drive 120/240 V plug to Spectrum® 240 V plug.



**XT60 Consumable Kit
256033**

Consumable kit
includes 3 standard
electrodes, 3 standard
tips, 1 drag shield, 1 deflector, 1 o-ring, 1 swirl
ring, 1 retaining cup, 1 gouge tip, 1 gouge
shield and silicone grease.




**Plasma Standoff Roller
Guide 253054**

Helps maintain
recommended standoff
distance to maximize
cutting performance
and improve tip life.



Plasma Circle-Cutting Guide 253055

Cut straight lines or circles up to 12-inch
diameter with ease.



Suction/Magnetic Pivot Base 195979

Add this to your cutting guide for convenient
attachment to all flat surfaces. The extended arm
accommodates holes up to 30-inch diameter.



RTI Filter and Bracket 300491

Dryer will remove water, dirt and oil
as small as one micron with 99.9
percent efficiency. Can be mounted
on plasma cutter or on wall. Install
as close as possible to point of
air consumption.

RTI Replacement Filter Element 212771

For RTI filter 300491.



In-Line Air Filter Kit 228926

Mounts to the back of the
Spectrum® 875 and 875 Auto-Line™.
Includes male and female 1/4-inch
NPT quick-disconnect fittings and
hose for easy on/off connection. The
replaceable filter element filters to .85 microns
for removal of 99.9 percent of water, dirt and oil.

**In-Line Air Filter Replacement Element
228928**

For in-line filter 228926.



Torch Cable Covers
239642 20 ft. (6.1 m)
231867 25 ft. (7.6 m)
231868 50 ft. (15.2 m)



Flexible Work Cable
234838 20 ft. (6.1 m)
234930 50 ft. (15.2 m)
Work cable with quick
connect and heavy-duty clamp.

Safety Glasses
(shade 5 lenses, recommended)



235658 Black frame
235657 Blue frame
235659 Orange frame
272209 Slag™ white frame

Form-fitting orbital eye coverage with increased
comfort and style. Meets ANSI Z87.1 standards.

Automation Accessories

For Spectrum 875 (single-phase)



Automation Kit 301156

Kit for single-phase Spectrum 875
works with both XT60M long and
short body machine torches to provide
automation capabilities. Includes
voltage sensing signal wire assembly
for torch height control. Also includes
the following components which can
also be ordered separately:

- **Jumper Plug 256574**
For changing back to hand-held torch after kit has been installed.
- **Internal Remote Harness 265527**
For remote start only.
- **CNC Signal Cable 220240**
For arc initiation and cutting sequence.
- **Shield Sense Tab 263310**

External Reed Switch 190602

Provides dry contact closure for ok-to-move signal.
(Not included with Automation Kit 301156.)

For Spectrum 875 Auto-Line




Automation Kit 301157

Kit for Spectrum 875
Auto-Line works with both
XT60M long and short body
machine torches to provide
automation capabilities.
Includes the following
components which can also
be ordered separately:

- **Internal Remote Harness 265528**
For remote start and ok-to-move signal.
- **CNC Signal Cable 220240**
For arc initiation and cutting sequence.
- **Voltage Sensing Signal Wire Assembly 246285**
For torch height control.
- **Remote Pendant Control 195513**
For remote manual momentary on/off.
- **Shield Sense Tab 263310**

Note: Automation Kits are for upgrading hand-held torch packages to add machine torch capabilities. Machine torches are not included in Automation Kits and must be ordered separately. See back page to order machine torches.

XT60 and XT60M Replacement Torches and Consumables



O-ring	263834
Swirl Ring	256028
Electrode	256026
Tip	249929 (60 A) 262643 (40 A)
Gouge Tip	249935
Retaining Cup	256029
Deflector	256030
Gouge Shield	256031
Drag Shield	256027

Note: Replacing drag shield with deflector offers improved arc visibility while maintaining 1/16-inch standoff. For gouging, replace the tip and drag shield with gouge tip and gouge shield. The rest of the XT60 consumables are common.

XT60 Hand-Held Torch
249953 20 ft. (6.1 m)
249954 50 ft. (15.2 m)

No-slip grip for easy control and torch dexterity.

Ergonomic design with unique thumb guide and finger grip contours.

Trigger guard protects against inadvertent arc initiation.

80-degree handle provides natural arm and elbow positioning while cutting.

Robust tip front end design optimizes arc performance and tip life.

Laser-etched tip for easy identification.

New retaining cup design provides increased cutting visibility and quick turn for easy consumable change.

Strain relief is durable and corrosion resistant, and **more flexible cable** has improved bend radius.



XT60M Machine Torch
249955 25 ft. (7.6 m), long body
249956 50 ft. (15.2 m), long body
257464 25 ft. (7.6 m), short body
263952 50 ft. (15.2 m), short body



Shield Sense Tab 263310
 Included in Automation Kits, not included with torches.

Machine Shield 265226

Note: The XT60M consumables are the same as the XT60 consumables, except for the machine shield.

Ordering Information

Power Source	Stock No.	Description	Qty.	Price
Spectrum® 875 208/230 V, 1-phase	907583	With 20 ft. (6.1 m) XT60 hand-held torch		
	907583001	With 50 ft. (15.2 m) XT60 hand-held torch		
	907583002	With 25 ft. (7.6 m) XT60M long body machine torch		
Spectrum® 875 Auto-Line™ 208 – 575 V, 1- or 3-phase	907584	With 20 ft. (6.1 m) XT60 hand-held torch		
	907584001	With 50 ft. (15.2 m) XT60 hand-held torch		
	907584002	With 25 ft. (7.6 m) XT60M long body machine torch		
	907584004	With 50 ft. (15.2 m) XT60M long body machine torch		
Replacement Torches and Consumables		See above		
Accessories				
Automation Accessories		See page 3 for kits and accessories		
Full KVA Adapter Cord	300517	Adapts engine drive 120/240 V plug to Spectrum® 240 V plug		
XT60 Consumable Kit	256033			
Plasma Standoff Roller Guide	253054			
Plasma Circle-Cutting Guide	253055			
Suction/Magnetic Pivot Base	195979			
RTI Filter and Bracket	300491			
RTI Filter Replacement Element	212771	For RTI filter 300491		
In-Line Air Filter Kit	228926			
In-Line Air Filter Replacement Element	228928	For in-line filter 228926		
Torch Cable Covers		See page 3		
Flexible Work Cable w/Heavy-Duty Clamp	234838	20 ft. (6.1 m) cable with quick connect		
	234930	50 ft. (15.2 m) cable with quick connect.		
Safety Glasses		See page 3		

Date:

Total Quoted Price:

Distributed by:

