## Welding Curtains

### Ordering your custom welding screens

Tillman ArcShield welding curtains are the professionals go-to choice to enclose robotic welding cells, welding workstations, partition maintenance areas, and isolate areas while keeping workers protected from weld flash burn, molten metal, and sparks. Tillman curtains are great for use on Tillman track mounted rolling curtains. Reach out to your distributor and let them help you select the right curtain to fit your needs.

- I. Specify the exact finished size, height, and width and add 10% to width for proper drape. Fractions of a foot will be billed to next full foot.
  - Actual finished size may vary 3" in height and width.
- 2. For ventilation, it is recommended to allow a 3"-12" gap between floor and bottom of curtains.

#### 3. Grommet placement:

- On curtains (C) 3/8" grommets are set every 12" along top and at each corner.
- On replacement curtains for screens (R) measuring less than 50 sq. ft., grommets are set on 12" centers on all sides.
- Let your distributor know if you desire different grommet spacing.

#### 4. Choose any accessories or add-ons

- CC3003 1/2 lb/ft chain sewn into bottom of the curtain hem to stabilize curtain.
- PN NEEDED Hook & loop material sewn on curtain edges for joining multiple curtains or creating an enclosure.
- CC3001 1" steel "S" hook 2 1/2" in length for hanging curtains on a pipe or cable up to a 1" diameter.
- CC3002 2" steel "S" hook 3 1/2" in length for hanging curtains on a pipe or cable up to a 2" diameter.

| Description  | 14 mil. Tranparent Vinyl Rolls |             |             |             |             |             |  |
|--|--------------------------------|-------------|-------------|-------------|-------------|-------------|--|
|  | Gray                           | Yellow      | Green       | Orange      | Blue        | Shade 8     |  |
| 64" Wide x 100 Yards (No grommets)                 | 600-64                         | 601-64      | 602-64      | 603-64      | 604-64      | 606-64      |  |
| 74" Wide x 86 Yards (No grommets)                  | 600-74                         | 601-74      | 602-74      | 603-74      | 604-74      | 606-74      |  |
|  |                                |             |             |             |             |             |  |
| Size (Width, Length)                               | 600-C (W,L)                    | 601-C (W,L) | 602-C (W,L) | 603-C (W,L) | 604-C (W,L) | 606-C (W,L) |  |
| Size w/ Grommets on all four sides (Width, Length) | 600-R (W,L)                    | 601-R (W,L) | 602-R (W,L) | 603-R (W,L) | 604-R (W,L) | 606-R (W,L) |  |

| Rolls  | 12 oz.<br>Olive Duck | 13 mil. Vinyl Coated Polyester |             |             | 16 Mil.     | 40 Mil.     |
|--|----------------------|--------------------------------|-------------|-------------|-------------|-------------|
|  |                      | Yellow                         | Dark Green  | Blue        | Clear       | Orange      |
| 60" Wide x 100 Yards                               | 583-60               |                                |             |             |             |             |
| 72" Wide x 100 Yards                               | 583-72               |                                |             |             |             |             |
| 61" Wide x 75 Yards                                |                      | 611-61                         | 612-61      | 614-61      |             |             |
| 72" Wide x 53 Yards                                |                      |                                |             |             | 605-72      |             |
| 48" Wide x 33 Yards                                |                      |                                |             |             |             | 623-48      |
|  |                      |                                |             |             |             |             |
| Size (Width, Length)                               | 583-C (W,L)          | 611-C (W,L)                    | 612-C (W,L) | 614-C (W,L) | 605-C (W,L) | 623-C (W,L) |
| Size w/ Grommets on all four sides (Width, Length) | 583-R (W,L)          | 611-R (W,L)                    | 612-R (W,L) | 614-R (W,L) | 605-R (W,L) | 623-R (W,L) |



WARNING: 583: This product can expose you to chemicals including Cumene and Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.



WARNING: 611, 612, 614: These products can expose you to chemicals including Di-Isononyl Phthalate, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.



# Let Tillman protect your employees from harmful UV flash and welding arc with Tillman's ArcShield pregrommeted welding curtain rolls.

Tillman's ArcShield pre-grommeted curtains offer grommets every 12" on the top & bottom and are ideal protection from welding hazards in areas such as MIG, TIG, plasma cutting, and grinding.

These pre-grommeted welding curtain rolls are ideal for applications where large curtains are needed to enclose the perimeter of a welding area. Installation is very easy; roll out the length of curtain required, cut it to size and hang with hooks or zip-ties.

Please note: the edge with the grommet does not have a reinforced hem. If weight is added to the curtain, the grommet could burst.

Tillman offers two widths - 64" & 74" both 25 yards long.

#### **Order notes:**

When ordering curtains, specify height first then width. Fractions of a foot will be billed to next full foot. Be sure to add 10% to width for proper drape. Actual finished size may vary 3" in height and width.

#### **Grommet placement:**

- 1. On curtains (C) grommets are set every 12" along top/bottom and at each corner. There is no border hems on pre-grommeted roles.
- 2. On replacement curtains for screens (R) measuring less than 50 sq. ft., grommets are set on 12" centers on all sides.

| Description                      | 14 mil. Trar | 14 mil. Transparent Vinyl, Pre-Grommeted |         |         |         |         |  |  |
|----------------------------------|--------------|--|---------|---------|---------|---------|--|--|
|                                  | Gray         | Yellow                                   | Green   | Orange  | Blue    | Shade 8 |  |  |
| 64" W, 25 yds., 48 lbs. per roll | 6002564      | 6012564                                  | 6022564 | 6032564 | 6042564 | 6062564 |  |  |
| 74"W, 25 yds., 54 lbs. per roll  | 6002574      | 6012574                                  | 6022574 | 6032574 | 6042574 | 6062574 |  |  |