

PAINTER'S TAPES

CF 120



**FROGTAPE® MULTI-SURFACE
MEDIUM ADHESION
RUBBER-BASED ADHESIVE
EXCLUSIVE PAINTBLOCK® TECHNOLOGY**

TENSILE (LBS/IN WIDTH)	22
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
THICKNESS (MILS)	5.7
ELONGATION (%)	10
MAXIMUM SERVICE TEMPERATURE (°F)	-
APPLICABLE STANDARDS*	16

For interior or exterior use on multiple surfaces, including cured painted walls, wood trim, glass and metal; Withstands direct sunlight for up to 7 days.



CF 160



**FROGTAPE® DELICATE SURFACE
LOW ADHESION
ACRYLIC-BASED ADHESIVE
EXCLUSIVE PAINTBLOCK® TECHNOLOGY**

TENSILE (LBS/IN WIDTH)	23
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	14
THICKNESS (MILS)	3.6
ELONGATION (%)	4.5
MAXIMUM SERVICE TEMPERATURE (°F)	-
APPLICABLE STANDARDS*	-

For interior use on freshly painted surfaces (24 hours old), faux finishes, primed wallboard and wallpaper.



CP 130



**FROGTAPE® PRO GRADE
MEDIUM ADHESION
RUBBER-BASED ADHESIVE
EXCLUSIVE PAINTBLOCK® TECHNOLOGY**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS (MILS)	5.5
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	-

For interior or exterior use on multiple surfaces, including cured painted walls, wood trim, glass and metal.



CP 27®



**PREMIUM GRADE, SHURRELEASE®
MEDIUM ADHESION
SYNTHETIC RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	32
THICKNESS (MILS)	5.5
ELONGATION (%)	9
MAXIMUM SERVICE TEMPERATURE (°F)	200
APPLICABLE STANDARDS*	-

For interior and exterior use on multiple surfaces, including painted walls, glass, vinyl, metal and wood; Not recommended for use on wallpaper, unpainted wallboard, ceiling tile or with uncured coatings.



CP 150



**PAINTER'S MATE GREEN®
MEDIUM ADHESION
RUBBER-BASED ADHESIVE**

TENSILE (LBS/IN WIDTH)	21
ADHESION TO STAINLESS STEEL (OZ/IN WIDTH)	30
THICKNESS (MILS)	4.6
ELONGATION (%)	10
MAXIMUM SERVICE TEMPERATURE (°F)	150
APPLICABLE STANDARDS*	16

For interior use on painted walls, woodwork, glass, metal and vinyl.

