

POWER MIG® 256

POWER MIG® with Precision Control

- Ideal for light industrial and maintenance work
- Weld up to 3/4 in. (19.1 mm) mild steel with self-shield flux-cored wire
- Digital meters help dial in exact settings and timer functions deliver additional weld control
- Spool gun ready for our premium Magnum® PRO 250LX



Processes

- MIG
- Flux-Cored

Output



Input



Literature

E7.55

Product Name	Product Number	Input Power Voltage/Phase/Hertz	Rated Output: Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	Wire Feed Speed ipm (m/min)	H x W x D in (mm)	Net Wt. lb (kg)
POWER MIG® 256	K3068-1	208/230/1/60	250A/26V/40%	56/52A ⁽¹⁾	30-300A	50-700 (1.3-17.7)	31.8 x 18.9 x 38.8 (808 x 480 x 985)	220 (100)
	K3068-2 ⁽²⁾	230/460/575/1/60		50/24/19A				
One-Pak® w/Spool Gun	K3069-1	208/230/1/60		56/52A ⁽¹⁾			—	—

⁽¹⁾Input current is at the rated output with the 115V auxiliary receptacle also drawing 15 amps. ⁽²⁾Does not include input cable.

WARNING: Cancer and Reproductive Harm -www.P65Warnings.ca.gov

POWER MIG® 260

Fabrication Simplified

- Ready. Set. Weld® Quick Set Up
- ArcFX™ Technology
- Universal Input Voltage
- Memory Capability
- Auto Calibration for Push-Pull Aluminum Performance



Processes

- MIG
- Flux-Cored

Output



Input



Literature

E7.56

Product Name	Product Number	Input Power Voltage/Phase/Hertz	Rated Output: Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	Wire Feed Speed ipm (m/min)	H x W x D in (mm)	Net Wt. lb (kg)
POWER MIG® 260	K3520-1	208/230/460/575/1/60	250A/26.5V/40%	59/55/27/21	30-300A	50-700 (1.3-17.7)	37.3 x 18 x 40.4 (947 x 457 x 1026)	247 (112)

WARNING: Cancer and Reproductive Harm -www.P65Warnings.ca.gov