

CONTACT TIPS

CONTACT TIPS 100 A				
Wire Diameter in. (mm)	Standard		Tapered	
	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100
0.025 (0.6)	KP11-25	KP11-25-B100	KP11T-25	—
0.030 (0.8)	KP11-30	KP11-30-B100	KP11T-30	—
0.035 (0.9)	KP11-35	KP11-35-B100	KP11T-35	—
0.035 (0.9) Aluminum	KP2078-1B1 ⁽¹⁾	—	—	—
0.045 (1.2)	KP11-45	KP11-45-B100	KP11T-45	—

⁽¹⁾ Recommended for aluminum wire welding.



CONTACT TIPS 200 A and 250 A								
Wire Diameter in. (mm)	Standard		Heavy Duty		Tapered		Notched	
	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100
0.025 (0.6)	KP14-25	KP14-25-B100	—	—	KP14T-25	—	—	—
0.030 (0.8)	KP14-30	KP14-30-B100	—	—	KP14T-30	KP14T-30-B100	KP2010-3B1 ⁽¹⁾	—
0.035 (0.9)	KP14-35	KP14-35-B100	KP14H-35	KP14H-35-B100	KP14T-35	KP14T-35-B100	KP2010-4B1 ⁽¹⁾	—
0.040 (1.0)	KP14-40	—	KP14H-40	KP14H-40-B100	KP14T-40	KP14T-40-B100	—	—
0.045 (1.2)	KP14-45	KP14-45-B100	KP14H-45	KP14H-45-B100	KP14T-45	KP14T-45-B100	—	—
3/64 (1.2)	KP14A-364 ⁽¹⁾	KP14A-364-B100 ⁽¹⁾	KP14AH-364 ⁽¹⁾	KP14AH-364-B100 ⁽¹⁾	—	—	KP2010-5B1 ⁽¹⁾	—

⁽¹⁾ Recommended for aluminum wire welding.

CONTACT TIPS 300 A and 400 A								
Wire Diameter in. (mm)	Standard		Heavy Duty		Tapered		Notched	
	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100	Pkg. Qty. - 10	Pkg. Qty. - 100
0.025 (0.6)	KP14-25	KP14-25-B100	—	—	KP14T-25	—	—	—
0.030 (0.8)	KP14-30	KP14-30-B100	—	—	KP14T-30	KP14T-30-B100	KP2010-3B1 ⁽¹⁾	—
0.035 (0.9)	KP14-35	KP14-35-B100	KP14H-35	KP14H-35-B100	KP14T-35	KP14T-35-B100	KP2010-4B1 ⁽¹⁾	—
0.040 (1.0)	KP14-40	—	KP14H-40	KP14H-40-B100	KP14T-40	KP14T-40-B100	—	—
0.045 (1.2)	KP14-45	KP14-45-B100	KP14H-45	KP14H-45-B100	KP14T-45	KP14T-45-B100	—	—
3/64 (1.2)	KP14A-364 ⁽¹⁾	KP14A-364-B100 ⁽¹⁾	KP14AH-364 ⁽¹⁾	KP14AH-364-B100 ⁽¹⁾	—	—	KP2010-5B1 ⁽¹⁾	—
0.052 (1.3)	KP14-52	KP14-52-B100	KP14H-52	KP14H-52-B100	KP14T-52	KP14T-52-B100	—	—
1/16 (1.6)	KP14-116	KP14-116-B100	KP14H-116	KP14H-116-B100	KP14T-116	—	—	—
5/64 (2.0)	KP14-564	—	KP14H-564	—	—	—	—	—

⁽¹⁾ Recommended for aluminum wire welding.

CONTACT TIPS 500 A		
Wire Diameter in. (mm)	Solid Wire, Heavy Duty	
	Pkg. Qty. - 10	Pkg. Qty. - 100
0.035 (0.9)	KP15H-35	—
0.045 (1.2)	KP15H-45	—
0.052 (1.3)	KP15H-52	—
1/16 (1.6)	KP15H-116	—
5/64 (2.0)	KP15H-564	—
3/32 (2.4)	KP15H-332	—

CONTACT TIPS 600 A		
Wire Diameter in. (mm)	Heavy Duty	
	Pkg. Qty. - 10	Pkg. Qty. - 100
0.035 (0.9)	KP16S-35	—
0.045 (1.2)	KP16S-45	—
0.052 (1.3)	KP16S-52	—
1/16 (1.6)	KP16S-116	KP16S-116-B100
5/64 (2.0)	KP16S-564	KP16S-564-B100
3/32 (2.4)	KP16S-332	KP16S-332-B100
7/64 (2.8)	KP16S-764	—
1/8 (3.2)	KP16S-18	—